

### Specification

Model No.	PD-	PD-	PD-	PD-	PD-	PD-
	081500-SM	082000-SM	G081600-SM	F081600-SM	IEC082000-SM	IEC082001-SM
Power Rating	15A 125VAC	20A 125VAC	16A 250VAC	16A 250VAC	20A 125VAC or 16A 250VAC	20A 125VAC or 16A 250VAC
Output Receptacle Type	NEMA 5-15R x 8	NEMA 5-20R x 8	Schuko Sockets x 8	French Sockets x 8	IEC Combo x 8 C13/C15/C19/C2	IEC320 C13 x 6 IEC320 C19 x 2
Input Type	IEC320 C20 inlet					
Input Phase	Single Phase					
Finish	Black					
Front Display	Color LCD Display					
Mount Orientation	Horizontal					
Height	1U					
Network Connectivity	Yes					
Touch Screen Display	Yes					
Metered per Outlet	Yes					
Switched per Outlet	Yes					
Overload Protection	Yes					
Outlet Power Indicator	Indicating on TFT LCD					
Status Monitoring	Outlet current value warning can be set manually.					
IP	Dynamic IP / Static IP					
Daisy Chain Ports	USB x 2					
Ethernet Port	RJ45 x 1 with Ethernet Indicator; Gigabit Ethernet :10/100M					
Firmware Update Port	USB 2.0					
Operating Environment	-20 ~ 60°C					
Physical Dimensions	L.481.0 x W.44.2 x D.200.0 mm					